

TeSys Control

K Contact blocks - Time delays

Product references



Instantaneous auxiliary contact blocks				
Clip-on front mounting, 1 per control relay				
Connection	Composition		Reference	
Screw clamp terminals				
	2	–	LA1KN20	
	–	2	LA1KN02	
	1	1	LA1KN11	
	4	–	LA1KN40 ⁽¹⁾	
	3	1	LA1KN31 ⁽¹⁾	
	2	2	LA1KN22 ⁽¹⁾	
	1	3	LA1KN13 ⁽¹⁾	
	–	4	LA1KN04 ⁽¹⁾	
Spring terminals	2	–	LA1KN203	
	–	2	LA1KN023	
	1	1	LA1KN113	
	4	–	LA1KN403 ⁽¹⁾	
	3	1	LA1KN313 ⁽¹⁾	
	2	2	LA1KN223 ⁽¹⁾	
	1	3	LA1KN133 ⁽¹⁾	
	–	4	LA1KN043 ⁽¹⁾	
Faston connectors 1 x 6.35 or 2 x 2.8	2	–	LA1KN207	
	4	–	LA1KN407 ⁽¹⁾	
	3	1	LA1KN317 ⁽¹⁾	

Electronic time delay contact blocks				
■ Relay output with common point changeover contact, ~ or ≡ 240 V, 2 A maximum ■ Control voltage 0.85...1.1 Uc ■ Maximum switching capacity 250 VA or 150 W ■ Operating temperature -10...+ 60 °C ■ Reset time: 1.5 s during the time delay period 0.5 s after the time delay period				

Clip-on front mounting, 1 per control relay				
Voltage	Type	Timing range	Composition	Reference
V		s		
~ or ≡ 24...48	On-delay	1...30	1	LA2KT2E
~ 110...240	On-delay	1...30	1	LA2KT2U
Other versions		Electronic timers type RE4. Please consult your Regional Sales Office.		

⁽¹⁾ Block of 4 contacts for use on CA2K and CA3K.