

Cable to cable junction			IP65 IP67		Han® 3 A cable to cable housing ■ M20 output		
					Metal, grey	19 20 003 1750	
					Metal, black	19 37 003 1750	
					Plastic, grey	19 20 003 0720	
					Plastic, black	19 20 003 0727	
					EMC	19 62 003 1750	
			CAT. 5 CAT. 5e IP65 IP67		Han® 3 A RJ45 coupler ■ 8 poles		
					Metal, grey	09 45 215 1107	
					Metal, black	09 45 215 1110	
					Plastic, black	09 45 225 1107	
USB	Cable side			Han-Brid® USB insert ■ Compatible with USB cables		09 12 001 3091	
	Equipment			Han-Brid® USB insert USB extender			
						USB 3.0	09 12 001 2793
						USB 2.0	09 12 001 2794
Han® 3 A RJ45 kit	Cable side			Han® 3 A RJ45 connector ■ 8 IDC contacts, can be assembled in the field without tools ■ AWG 27-22 ■ Transmission rate: 10/100 Mbit/s and 1/10 Gbit/s		CAT. 6	
					Plastic version, black	09 45 125 1560	
					Metal version, grey	09 45 115 1560	
	Equipment			Han® 3 A RJ45 Panel feed through ■ RJ45 coupler ■ Transmission rate: 10/100 Mbit/s and 1/10 Gbit/s		CAT. 6	
						Plastic version, black	09 45 225 1560
						Metal version, grey	09 45 215 1560
				Metal version, grey, with self-closing cover	09 45 215 1562		

Han® 3 A Connector - Characteristics and advantages

For strength and versatility, the Han® industrial connector is used and recognized in the fields of machinery, robotics, transport and energy. You will find a version to suit whatever your needs for use in harsh industrial environments.

Han® 3 A is a compact version available in several versions:

- Standard (zinc with epoxy finish)
- Gray or black plastic (polycarbonate)
- Han® EMC for environments subject to electromagnetic disturbances
- Han-INOX® for increased resistance to saline environments
- Han® HPR for harsh external environments (IP69k)
- Han® Ex for zones exposed to explosion hazard

More than 100 inserts in the Han® 3 A size are available for connecting power, signals and data (copper, coaxial, fibre optic).

