

4 pole contactors - Double box terminals

Max. operating current		Horsepower AC3 according to UL 508				Electrical endurance	Power cont.	Control circuit								
Max. cont. current rating. AC1 A	Motors 460V 3Ph 50-60Hz AC3 A	220-240V hp	380-415V hp	440-480V hp	550-600V hp	Cat. AC1 Operations	NO	NC	AC			AC/DC			Pack	
									Voltage ⁽¹⁾	Cat. no.	Ref. no.	Voltage	Cat. no.	Ref. no.		
90	50	15	30	30	40	1.5x10 ⁶	4	0	12	EF50A400B012	270095					5
									24	EF50A400B024	270096	24-60	EF50E400B24-60	270137	5	
									48	EF50A400B048	270098				5	
									110	EF50A400B110	270100	48-130	EF50E400B48-130	270138	5	
									208	EF50A400B208	270101				5	
									230	EF50A400B230	270102	100-250	EF50E400B100-250	270139	5	
									400	EF50A400B400	270103	250-500	EF50E400B250-500	270140	5	
									480	EF50A400B480	270105				5	
									575	EF50A400B575	270107				5	
									600	EF50A400B600	270108				5	
110	80	25	50	50	60	1.5x10 ⁶	4	0	12	EF80A400B012	270109					5
									24	EF80A400B024	270110	24-60	EF80E400B24-60	270141	5	
									48	EF80A400B048	270112				5	
									110	EF80A400B110	270114	48-130	EF80E400B48-130	270142	5	
									208	EF80A400B208	270115				5	
									230	EF80A400B230	270116	100-250	EF80E400B100-250	270143	5	
									400	EF80A400B400	270117	250-500	EF80E400B250-500	270144	5	
									480	EF80A400B480	270119				5	
									575	EF80A400B575	270121				5	
									600	EF80A400B600	270122				5	
140	95	30	60	60	75	1.5x10 ⁶	4	0	12	EF95A400B012	270123					5
									24	EF95A400B024	270124	24-60	EF95E400B24-60	270145	5	
									48	EF95A400B048	270126				5	
									110	EF95A400B110	270128	48-130	EF95E400B48-130	270146	5	
									208	EF95A400B208	270129				5	
									230	EF95A400B230	270130	100-250	EF95E400B100-250	270147	5	
									400	EF95A400B400	270131	250-500	EF95E400B250-500	270148	5	
									480	EF95A400B480	270133				5	
									575	EF95A400B575	270135				5	
									600	EF95A400B600	270136				5	



(1) Voltage 110V covers 110V 50-60Hz and 120V 60Hz.

Order codes

A

B

C

X

